



SAFETY DATA SHEET

Section 1. Identification of the material and the supplier

Product: **Dinitrol 447 Aerosol**
Product Use: Coating
Restriction of Use: Refer to Section 15

New Zealand Supplier: **Auto Body Equipment**
Address: 17 The Boulevard
Te Rapa, Hamilton, 3200
New Zealand

Telephone: +64 7 849 3514
Email: office@abe.co.nz
Emergency No: 0800 764 766 (National Poison Centre)

Date of SDS Preparation: 10 April 2018

Section 2. Hazards Identification

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval No: Aerosols (Flammable) – HSR002515

Pictograms



Flammable Irritant Chronic Ecotoxic

Signal Word: **DANGER**

HSNO Classes	Hazard Code	Hazard Statement	GHS Category
2.1.2A	H222	Extremely flammable aerosol.	Flam. Aero. 1
6.1E (dermal)	H313	May be harmful in contact with skin.	Acute Tox. 5
6.3A	H315	Causes skin irritation.	Skin Irrit. 2
6.4A	H319	Causes serious eye irritation.	Eye Irrit. 2A
6.5B	H317	May cause an allergic skin reaction.	Skin Sens. 1
6.8B	H361	Suspected of damaging fertility or the unborn child	Repr. 2
6.9B	H373	May cause damage to organs through prolonged or repeated exposure.	STOT RE 2
6.9N	H336	May cause drowsiness or dizziness.	STOT SE 3
9.1B	H411	Toxic to aquatic life with long lasting effects.	Aquatic Chronic 2

Prevention Code	Prevention Statement
P102	Keep out of reach of children.
P103	Read label before use.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames or hot surfaces. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P260	Do not breathe fumes, mist, vapours or spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective PPE as detailed in Section 8.
P281	Use personal protective equipment as required.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P362	Take off contaminated clothing and wash before re-use.
P391	Collect spillage.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.

Storage Code	Storage Statement
P405	Store locked up.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

Section 3. Composition / Information on Hazardous Ingredients

Ingredients	Wt%	CAS NUMBER.
Naphtha (petroleum), hydrotreated light	10-<25	64742-49-0
Xylene, mixed isomers, pure	10-<25	1330-20-7
Propane Liquefied	10-<25	74-98-6
Propane Liquefied	10-<25	74-98-6
Ethyl acetate	5-<10	141-78-6
Naphtha (petroleum), hydrotreated heavy	5-<10	64742-48-9
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	1-<5	64742-82-1
Ethanol	1-<5	64-17-5
Solvent naphtha (petroleum), light arom.	<1	64742-95-6
n-Hexane	<1	110-54-3
Gom Resin	<1	8050-09-7

Section 4. First Aid Measures

Routes of Exposure:

If in Eyes Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.

If on Skin	Take off contaminated clothing and wash before re-use. Immediately wash with water and soap and rinse thoroughly. If skin irritation or rash occurs: get medical advice/attention.
If Swallowed	Rinse mouth. Wash out mouth thoroughly with water. Never give anything to the mouth of an unconscious person. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Call a POISON CENTER if unwell.
If Inhaled	Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Apply artificial respiration if not breathing. Get medical advice if breathing becomes difficult.

Most important symptoms and effects, both acute and delayed

Symptoms:	Headache, dizziness and breathing difficulty.
Ingestion:	Not applicable.
Inhalation:	Not applicable.
Skin:	May be harmful if in contact with skin. Causes skin irritation.
Eye:	Causes eye irritation.
Chronic:	Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. Prolonged or repeated exposure may cause damage to the organs.

Section 5. Fire Fighting Measures

Hazard Type	Flammable Aerosol
Hazards from decomposition products	Carbon monoxide (CO) Nitrogen oxides (NOx)
Suitable Extinguishing media	CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Do not use water with full jet.
Precautions for firefighters and special protective clothing	Protective equipment: Mount respiratory protective device. Cool endangered receptacles with water spray.
HAZCHEM CODE	2YE

Section 6. Accidental Release Measures

Wear protective gear as detailed in Section 8. Evacuate all unnecessary personnel. Ensure adequate ventilation. Keep away from ignition sources.

Do not allow product to reach sewage system or any water course.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).. Do not flush with water or aqueous cleansing agents.

Dispose of waste according to the applicable local and national regulations.

Section 7. Handling and Storage

Precautions for Handling:

- Keep out of reach of children.
- Read label before use.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat, sparks, open flames or hot surfaces. No smoking.

- Do not spray on an open flame or other ignition source.
- Pressurized container: Do not pierce or burn, even after use.
- Do not breathe fumes, mist, vapours or spray.
- Wash hands thoroughly after handling.
- Use only outdoors or in a well-ventilated area.
- Contaminated work clothing should not be allowed out of the workplace.
- Open and handle receptacle with care.
- Avoid release to the environment.
- Wear protective PPE as detailed in Section 8.
- Use personal protective equipment as required.

Precautions for Storage:

- Store away from incompatible materials listed in Section 10.
- Store locked up.
- Store in a well-ventilated place. Keep container tightly closed.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C.
- Do not seal receptacle gas tight.

Section 8 Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance	TWA		STEL	
	ppm	mg/m ³	ppm	mg/m ³
Propane [74-98-6]	Simple asphyxiant – may present an explosion hazard			
Butane [106-97-8]	800	1,900	-	-
Xylene (o-, m-, p-isomers) [1330-20-7]	50	217		
Ethyl acetate [141-78-6]	200	720		
Ethyl alcohol (Ethanol) [64-17-5]	1,000	1,880		
Hexane (n-Hexane) (bio) [110-54-3]	20	72		

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices NOV 2017 9TH EDITION.

DNELs		
64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	Acute - systemic effects, general population	125 mg/kg bw/day (General Population)
Dermal	Acute - systemic effects, general population	125 mg/kg (General population)
	Long-term - systemic effects, worker	208 mg/kg bw/day (Worker)
Inhalation	Acute - systemic effects, general population	900 mg/m³ (General Population)
	Long-term - systemic effects, worker	871 mg/m³ (Worker)
106-97-8 Butane, pure		
WEL	Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)	

Engineering Controls

Ensure there is adequate ventilation available.

Personal Protection Equipment



Eyes	Tightly sealed goggles with side shields. Avoid wearing contact lenses.
Hands	Material of gloves: Nitrile rubber Penetration time of glove material > 480 min.
Skin	Body protection: Protective work clothing
Respiratory	In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Filter A/P2
General	Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the skin. Avoid close or long term contact with the skin. Avoid contact with the eyes and skin.

Section 9 Physical and Chemical Properties

Form	Aerosol
Colour	Black
Odour	Characteristic
Odour Threshold	Not available
pH	Not available
Boiling Point	Not available
Melting Point	Not available
Freezing Point	Not available
Flash Point	<-10 °C (DIN 53213)
Flammability	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Upper and Lower Explosive Limits	0.8% - 10.9% (vol)
Vapour Pressure @20°C	4000 hPa
Density@ 20°C	0.82 g/cm ³ (DIN 51757)
Specific Gravity	Not available
Water Solubility	Not miscible or difficult to mix.
Partition Coefficient:	Not available
Ignition Temperature	200°C
Decomposition Temperature	Not available
Kinematic Viscosity @20°C	Not available
Particle Characteristics	Not available
Solvent content	Organic Solvents: 68.8%
Solids content	30.9% (DIN 53216)
VOC(EU)	68.80%
VOC(EU)	565.0g/L
VOCV	68.80%

Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reactions known.
Conditions to Avoid	Keep away from heat, sparks, open flames or hot surfaces. No smoking. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Incompatible Materials	Combustible materials, oxidising agents
Hazardous Decomposition Products	Carbon monoxide.

Section 11 Toxicological Information**Acute Effects:**

Swallowed	Not applicable.
Dermal	May be harmful in contact with skin.
Inhalation	May cause drowsiness or dizziness.
Eye	Causes serious eye irritation.
Skin	Causes skin irritation. May cause an allergic skin reaction.

Chronic Effects:

Carcinogenicity	Not applicable.
Reproductive Toxicity	Suspected of damaging fertility or the unborn child.
Germ Cell Mutagenicity	Not applicable.
Aspiration	Not applicable.
STOT/SE	Not applicable.
STOT/RE	May cause damage to organs through prolonged or repeated exposure.

Acute Toxicity -

Chemical Name	LD50 (Oral)	LD50 (Dermal)	LC50 (inhalation)
Product			
64742-48-9 Naphtha (petroleum), hydrotreated	>5000mg/kg(Rat)	>3000mg/kg(Rat)	
106-97-8 Butane, pure			658mg/l 4h (Rat)
1330-20-7 Xylene, mixed isomers, pure	8700mg/kg (Rat)	2000mg/kg(Rabbit)	6350mg/l(Rat)
64742-49-0 Naphtha (petroleum), hydrotreated light	>5000mg/kg(Rat)	>2600mg/kg(Rabbit)	>193mg/l(Rat)
141-78-6 Ethyl acetate	4935mg/kg(Rabbit)		1600mg/l(Rat)
64-17-5 Ethanol	7060mg/kg(Rat)		20000mg/kg(Rat)
64742-82-1 Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics	>5000mg/kg(Rat)	>3000mg/kg(Rabbit)	2.8mg/l(Rat)
64742-95-6 Solvent naphtha (petroleum), light arom.	>6800mg/kg(Rat)	>3400mg/kg(Rat)	>10.2mg/l(Rat)

Section 12. Ecotoxicological Information

HSNO Classes: 9.1B = Toxic to aquatic life with long lasting effects.

Persistence and degradability	No data available
Bioaccumulation	No data available
Mobility in Soil	No data available
Other adverse effects	Slightly hazardous for water. Do not allow undiluted product to reach ground water, water course or sewage system.

Aquatic toxicity:

64742-49-0 Naphtha (petroleum), hydrotreated light
EC50/48 h 10 mg/l (PHAEOPHYTA)

Do not allow to enter waterways.

Section 13. Disposal Considerations**Disposal Method:**

Spent media that has removed toxic chemicals should be examined for specific hazards. Spilled product may be recovered for use if it has not come in contact with liquids or been exposed to significant amounts of gaseous contaminants. Dispose of according to Local Regulations.

Ensure any container holding waste product or contaminated spill media is labelled "Hazardous Waste – Flammable Aerosol, Ecotoxic" and that the label also has the Flammable, Ecotoxic Pictogram, waste type identifier, and the business name, address, and phone number.

Precautions or methods to avoid: Avoid release to the environment.

Section 14 Transport Information

This product is classified as a Dangerous Good for transport in NZ ; NZS 5433:2012

Road and Rail Transport

UN No: 1950
Class-primary 2
Proper Shipping Name: AEROSOLS

Air Transport

UN No: 1950
Class-primary 2
Proper Shipping Name: AEROSOLS

Marine Transport

UN No: 1950
Class-primary 2
Proper Shipping Name: AEROSOLS

Section 15 Regulatory Information**New Zealand:**

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval Code: Aerosols (Flammable) – HSR002515

HSNO Classification: 2.1.2A, 6.1E(Dermal), 6.3A, 6.4A, 6.5B, 6.8B, 6.9B, 6.9N, 9.1B

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	3000L (AWC)
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	1000L (9.1B)
Emergency Response Plan	1000L (9.1B)
Secondary Containment	1000L (9.1B)
Fire Extinguishers	>3000(AWC) (require 1x)
Restriction of Use	Only use for the intended purpose.

Glossary

EC ₅₀	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC ₅₀	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD ₅₀	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

References:

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2012
5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact Auto Body Equipment, if further information is required.

Issue Date:

10 April 2018

Review Date:

10 April 2023