


# Technical Data Sheet

<p><b>General</b></p> <p>Article number:          206021 (21 cm)          206028 (28 cm)          206037 (37.5 cm)          206045 (45 cm)          206060 (60 cm)          206090 (90 cm)          2060120 (120 cm)          2060150 (150 cm)</p> <p>Description: Masking Paper Premium, Recycled Paper,          300 meter rolls 50g.</p>	
---	---

Specification	Conform	Unit	Standard	Max.	Min.
Substance:	ISO 536	g/m <sup>2</sup>	50.0 g	52.5	47.5
Bursting strength:	ISO 2758	kPa.m <sup>2</sup> /g	2.2	-	1.9
Porosity:	ISO 5636-3 (Bendtsen)	ml/min	120	150	-
Water absorption:	ISO 535 (Cobb)	g/m <sup>2</sup>	22	25	-

## General specifications

Reel width:	+/- 1 mm
Reel diameter:	indication max. -5% of diameter otherwise +/-5% of diameter
Reel hardness	min. 30% without crepe paper
Heat stability:	200 – 250° C when using a cylinder.
Core:	5.0 cm 7.0 cm 7.6 cm 10.0 cm
Core diameter:	+/- 2 mm
Telescoped reel:	+/- 1 mm
Tight edges:	+/- 1% of diameter
Machine direction:	by means of arrow
Joints:	max. 2 per reel
Roll length:	300 meter
Pallets:	150 rolls (206021) 120 rolls (206028) 90 rolls (206037) 60 rolls (206045, 206060, 206090) 30 rolls (2060120, 2060150)

## Remarks

Colad Masking Paper has customized properties for use in diverse masking applications. This makes the paper easy in use and also optimized masking capabilities. Perfect barrier properties in combination with the right absorption possibilities: paint will stick to the Masking Paper, but will not bleed through under normal conditions.

For easy application of Colad Masking Paper, different aprontapers are available.

**Related products**

Article number: 9004xx

Description: Colad Aqua Dynamic Masking Tape

**Created by:**

EMM International BV

Bohemensstraat 19, 8028 SB Zwolle, The Netherlands

[www.emm.com](http://www.emm.com)

T +31(0)38 467 66 00

[www.colad.co](http://www.colad.co)